


Performance characteristics:

1. Main body part material
Insulator: PA66 Nature UL94V-0
2. Electrical requirements:
Current rating: 3 A
Voltage rating: 250 V
Insulation resistance: ≥1000 MΩ
Withstanding voltage: 1000 Vr.m.s, 1mA, 60s
- ③ 3. Environment specification
Working temperature: -40°C ~ +105°C
4. Packing & storing
Method of packing: Plastic bag, inner box, outer box
Storing condition: Temperature of -10°C ~ +40°C
below 80% relative humidity
5. Style of installation: Applicable for crimp cable installation
6. To prevent the pollution of the environment product info
RoHS agreement: Content

Size table:

P/N	Pin number	A	B	C
e3431029	2	7.30	5.70	2.50
e3431030	3	9.80	8.20	5.00
e3431031	4	12.30	10.70	7.50
e3431032	5	14.80	13.20	10.00
e3431033	6	17.30	15.70	12.50
e3431034	7	19.80	18.20	15.00
e3431035	8	22.30	20.70	17.50
e3431036	9	24.80	23.20	20.00
e3431037	10	27.30	25.70	22.50
e3431038	11	29.80	28.20	25.00
e3431039	12	32.30	30.70	27.50
e3431040	13	34.80	33.20	30.00
e3431041	14	37.30	35.70	32.50
e3431042	15	39.80	38.20	35.00



Unless otherwise specified tolerance:

X.	± 0.50	X.°	± 3°
.X	± 0.38	.X°	± 2°
.XX	± 0.25		

					2.50mm Pitch wafer female housing		wrj-e343			
Mark	NO.	File NO.	Signature	Date			Projection	Rev.	Weight	Scale
③	1	SN-00003561	An.Cheng	2014.04.18						
DRAW	J.A 2009-02-28									
CHK										
MAN										
STD										
APP										
					e3431xxx		Sheet 1 1 of 1			
							深圳市威尔杰电子有限公司			